

CFB9604 – "LDPE Pink AS"

Specification Sheet

This anti-static product is specially designed for packaging applications that require exceptional cleanliness and that meet the requirements of anti-static film. Our anti-static poly film is AMINE FREE and is available in colors.

Material:	Virgin Custom Polyethylene
Available As:	Lay-flat Tubing, Sheeting & Bags
Clarity:	Transparent or color

	Value	Specification
Density (Specific	.924	ASTM D
Gravity)		1505
Gauge, Gauge	2 mil, +/- 10%	ASTM D 374
Tolerance		
Tensile Strength @		ASTM D 882
Break	_	
MD	2900 PSI	
TD	2600 PSI	
Elongation Strength		ASTM D 882
MD	220%	
TD	330%	
Dart Impact	80 Grams	ASTM D
		1709
Cleanliness	Level 100	NASA
		JPG5322.1
	Level 100	IEST-STD
	11	CC1246D
Surface Resistivity	<10 ¹¹	ASTM D 257
	OHMS/SQ.	
_		
Tear resistance		ASTM D
(Elmendorf)		1922



CFB9604 – "LDPE Pink AS"

Specification Sheet (cont.)

Leachable Anions by IC

Analyte	Reporting Limit (ng/cm²)	Sample Results (ng/cm²)
Bromide	0.2	*
Chloride	0.1	0.2
Flouride	0.03	*
Nitrate	0.2	*
Nitrite	0.1	*
Phosphate	0.2	*
Sulfate	0.2	*

^{* -} Reported results are less than the reporting limit

Leachable Monovalent & Divalent Cations by IC

Analyte	Reporting Limit (ng/cm²)	Sample Results (ng/cm²)
Lithium	0.2	*
Sodium	0.1	*
Ammonium	0.2	*
Potassium	0.2	*
Magnesium	0.2	*
Calcium	0.2	*

^{* -} Reported results are less than the reporting limit

NVR

11121	
"LDPE PAS" Sample	10.3 ug/cm ²



CFB9604 - "LDPE Pink AS"

Specification Sheet (cont.)

Leachable Laser Particle Count

Leaching Volume=300 ml / Surface Area=948 cm² / Leaching Time = 1 HR.

	Measured (counts/cm ²)
Particles >= 0.3 um	470
Particles >= 0.5 um	75
Particles >= 0.75 um	25
Particles >= 1.0 um	7.4
Particles >= 2.0 um	1.5
Particles >= 5.0 um	0.2