





Providing the comfort and coolness of a ventilated back, SHOWA 376 combines a foam grip with a seamless liner to create outstanding performance in the most demanding conditions.

## **FEATURES**

- 13-gauge seamless knit liner
- Black absorbent foam nitrile palm coating
- Thin dipped blue nitrile 3/4 hand coating
- Extra-long color coded elastic wrist



- Superior foam over-dip ensures excellent grip even in oily applications
- Liquid resistant to end of coated area
- Warmth, protection and comfort
- Thin nitrile coating offers splash protection against wide range of chemical substances

## **INDUSTRY**



Airports & Ports



Automotive



Mechanical



Oil and Gas



Railways




Utilities



Warehousing and Distribution





## IDEAL APPLICATIONS

- Automotive repairs and maintenance
- Light assembly of oil-coated pieces
- Mechanical engineering
- Handling heavy equipment
- Drainage, piping
- Shipping/Receiving



### **MATERIAL**

- Polyester
- Seamless knit

### **COATING**

• Foam nitrile

#### **GRIP**

Foam

### **STANDARDS**







# GENERAL PURPOSE | LIQUIDS



SHOWA

376



### **PACKAGING**

- 12 Pair per polybag6 Polybags per case
- 72 Pair per case





- S
- M
- L
- XXL



### **COLOUR**

• Black / blue coating w/black palm



# YOU MIGHT ALSO BE INTERESTED IN

377



MATERIAL
Polyester
COATING
Foam nitrile

SHOWA 377-IP



Nylon
COATING
Foam nitrile

SHOWA S-TEX 377



Nylon
COATING
Foam nitrile

381



MATERIAL
Microfiber
COATING
Foam nitrile

# **USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. Do not use where there are electrical, thermal or entanglement risks. Discard used gloves in compliance with local regulations. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance. Store in a dry place, away from the light

### DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

