





SHOWA

8814

Designed to withstand heat exposure and multiple washings while maintaining superior tactile dexterity, SHOWA 8814 protects you from intermittent heat up to 500°F.

FEATURES

- Non-woven liner
- 14" long 355mm long
- Black color
- Textured coating
- Slip-on design



BENEFITS

- Protection against intermittent heat up to 500°F 260°C
- Textured surface provides better grip
- Easy to put on and remove
- Impermeable for working in damp or greasy environments

INDUSTRY



Automotive



Food



Metallurgy

IDEAL APPLICATIONS

- Automotive repairs and maintenance
- Mechanical and engineering
- Metal Stamping
- Bakeries & delicatessens
- Casting



TAA PRODUCTS

MATERIAL

- Cut and sewn
- Non woven liner

COATING

Neoprene

GRIP

Rough

STANDARDS















8814







● M ● L







YOU MIGHT ALSO BE INTERESTED IN

SHOWA **6781R**



MATERIAL Cotton COATING chemical resistant

SHOWA **6781R-145**



Cotton
COATING
chemical
resistant

SHOWA **240**



MATERIAL Glass Fiber COATING Neoprene

SHOWA **4561**



MATERIAL Kevlar COATING Foam nitrile

USER INSTRUCTIONS

Do not use where there are electrical, thermal or entanglement risks. Discard used gloves in compliance with local regulations. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance. Store in a dry place, away from the light.

Do not use where there are chemical, electrical or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. Store in a dry place, away from the light. Gloves must not come in contact with an open flame.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

