

System 230

System 230 Binocular Microscopes



LX Microscopes by UNITRON's System 230 is a full featured binocular microscope system with a sealed polymer body. It is the perfect solution for economically budgeted production applications. Designed and intended for lighter duty usage in assembly, rework, and limited inspection processes. Featuring a 20mm optics system, it fits many applications where higher magnification isn't required.

A Solution for Every Application

LX Microscopes by UNITRON feature high-quality achromatic lenses with anti-reflective coatings for superior visual clarity. Optional eyepieces and accessory objective lenses can be added to provide a wider range of magnification. A choice of light sources and mounting options enable the product set-up best suited for each individual application. Digital imaging systems are configurable to allow capturing of images to catalog or share inspection results and observations, for archiving or communicating electronically. The end result is increased productivity with an easy-to-use product line.

TECHNICAL DESCRIPTION

OPTICS

20mm, 10X widefield eyepieces with individual diopter adjustment and eyeshields. 97mm working distance (with included 1.0X lens) 180 mm (over 7") when used with an optional 0.5X reducing lens.

MAGNIFICATION

Standard 7X-30X magnification range

LENSES

High-quality achromatic lenses with anti-reflective coatings

ERGONOMICS

Standard 45° viewing angle

ZOOM

0.7X - 3X zoom range (4.3:1 zoom ratio) controlled by dual graduated knobs located on both sides of the head

CONSTRUCTION

Sealed polymer body

MOUNTING

Dual boom ball bearing stand with 15'' vertical post and 22.5'' horizontal ($11.1'' \times 10.25''$ base); single boom stand with 20'' vertical post and 22'' horizontal ($15'' \times 10''$ base); non-illuminated plain stand with 12.5'' vertical track and 3.9'' focus travel.

Additional lighting options sold separately.

5 Year Warranty - please refer to our website for details.

Design, features and specifications are subject to change without notice





| SYSTEM 230 CONFIGURATIONS | | | | | |
|---------------------------|----------------------|---|--|--|--|
| Part number | Microscope | Description | | | |
| 20714BB | System 230BB | S-Z 20mm Binocular, BB Stand | | | |
| 20780BB | System 230BB-LED3000 | S-Z 20mm Binocular, BB Stand, LED-3000 Ring Light | | | |
| 20716BB | System 230BB-LEDQRL | S-Z 20mm Binocular, BB Stand, Quadrant LED Ring Light | | | |
| 20717BB | System 230BB-LEDECO | S-Z 20mm Binocular, BB Stand, LED-ECO Ring Light | | | |
| 20714 | System 230 | S-Z 20mm Binocular, Single Boom Stand | | | |
| 20780 | System 230-LED3000 | S-Z 20mm Binocular, Single Boom Stand, LED-3000 Ring Light | | | |
| 20716 | System 230-LEDQRL | S-Z 20mm Binocular, Single Boom Stand, Quadrant LED Ring Light | | | |
| 20717 | System 230-LEDECO | S-Z 20mm Binocular, Single Boom Stand, LED-ECO Ring Light | | | |
| 20784 | System 230PFS | S-Z 20mm Binocular, Non-Illuminated Plain Stand | | | |
| 20783 | System 230PFS-LEDECO | S-Z 20mm Binocular, Non-Illuminated Plain Stand, LED-ECO Ring Light | | | |
| 20750 | - | 0.5X Reducing Lens, 20mm (for System 230 models only) | | | |
| 20736 | - | 0.75X Reducing Lens, 20mm (for System 230 models only) | | | |

BALL BEARING BOOM STANDS









SINGLE BOOM STANDS









NON-ILLUMINATED PLAIN STANDS





REDUCING LENSES





SYSTEM 230 OPTICAL SPECIFICATIONS

| Objective | | | | | | |
|-----------|-----------------------------|--------------------|------------|---------------|--|--|
| Eyepieces | | 1.0X (included) | 0.5X | 0.75X | | |
| 10X | Total Magnification (Range) | 7X - 30X | 3.5X - 15X | 5.25X - 22.5X | | |
| | Field of View Diameter (mm) | 25.7 - 6 | 51.4 - 12 | 34.3 - 8 | | |
| | Working Distance (mm) | 97 | 180 | 120 | | |



