



# **SHOWA 892**

Forged with fluoroelastomer rubber, the SHOWA 892 chemical and acid resistant glove provides superior resistance to highly corrosive acids. The butyl rubber coating is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene. Smooth surface grip allows for increased sensitivity and tactility when handling small components.



#### **BENEFITS**

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable

# **FEATURES**

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

#### **INDUSTRIES**



Chemical

#### **HAZARDS**



Chemical

## **NORMS & CERTIFICATES**

Cat II

0299

EN 388:2016

1010X



:N 388:2016



DFL

EN ISO 374-5:2016



VIRUS

## **TRADES & APPLICATIONS**

- Chemical spray and treatment
- Coating preparation
- · Laboratory, pharma & analysis
- Painting & spray workshops
- Fracking
- Drilling





## **PACKAGING**

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

#### **LENGTH**

12 in

## **COATING**

Viton

#### **SIZES**

7/S | 8/M | 9/L | 10/XL | 11/XXL

#### **COLOUR**

Black

#### **MATERIAL**

Unsupported

#### **USER INSTRUCTIONS**

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

# DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.