

FEATURES:

- 5–65x Standard Magnification Range (up to 390x w/options)
- Super Wide 28mm High Eye Point and Wide Field Eyepieces
- Eye-tube Inclination of 45° with 360° Rotation of Main Body
- 195mm of Working Distance with 0.5x Objective Lens
- ±6 Diopter Adjustment Range
- Interpupillary Distance Adjustment on Eyepiece Tubes
- Trinocular Package includes 0.3x CCD Adapter

- All Trinocular Packages include our 5MP Hybrid HDMI/USB Camera with Advanced Onboard Imaging Controls
- Precision-glide Ball Bearing Arm Base Assembly
- 5 Year Mechanical Warranty (1 Year Electrical)

9 Languages Supported							
简体中文	한국어	Le Français					
繁体中文	Deutsch	日本語					
English	Italiano	El Español					

PROZOOM® PZ - 6.5 TECHNICAL DATA:

Eyepiece		Main Body	0.37 x PZ-OB-037	0.5 x PZ-OB-050	0.7 x PZ-OB-070	1.0 x PZ-OB-100	2.0 x PZ-OB-200
10x	MAG:	10-65x	3.7-24.1x	5-32.5x	7 - 64x	10-65x	30-130x
	FOV:	23-3.5mm	62.2 – 9.6mm	46-7mm	32.9-5mm	23-3.5mm	11.5 – 1.8mm
15.4	MAG:	15-97.5x	5.55 – 36.1x	7.5-48.8x	10.5-69x	15-97.5x	30-195x
15x	FOV:	17-2.6mm	45.9-7.mm	34-5.2mm	24.3 – 3.7mm	17-2.6mm	8.5 – 1.3mm
20	MAG:	20-130x	7.4-48.1x	10-65x	14-92x	20-130x	40-260x
20x	FOV:	14-2.2mm	37.8 – 5.8mm	28-4.2mm	20-3.1mm	14-2.2mm	7–1.1mm
30x	MAG:	30-195x	30-195x	11.1 – 72.2x	21–138x	30-195x	60-390x
	FOV:	9-1.4mm	24.3 – 3.7mm	18-2.7mm	12.9-2mm	9-1.4mm	4.5 – 0.7mm
Working Distance		118mm	275mm	195mm	145mm	110mm	35mm





IMAGE CAPTURE

Still Image & Video 8GB SD Card



CALIBRATED MEASURE

No PC Required! Export to Database



REAL TIME COMPARE

Live Image vs Captured See the Difference



ULTRA-HIGH SENSITIVITY

Industry Leading Low Light Performance



EXTENDED DEPTH OF FOCUS



high clarity image.



Inspecting something that is just too big to view all at once? Capture multiple images of the object, then 'stitch' them together digitally to create a single extra-large image.

	Mounting Base		Digital Video	Light Source		
Part Number	Articulating Arm	Heavy Duty Ball Bearing	5MP Hybrid Camera	Fluorescent Ring	150W Fiber Optic	LED
TKPZ-A		✓			Annular Ring	
TKPZ-BL		✓			Back Light	
TKPZ-D		✓			Dual Point	
TKPZ-F		1		✓		
TKPZ-FA-A	✓				Annular Ring	
TKPZ-FA-BL	✓				Back Light	
TKPZ-FA-D	✓				Dual Point	
TKPZ-FA-F	✓			✓		
TKPZ-FA-LV2	✓					✓
TKPZ-LV2		✓				✓
TKDPZT-A		✓	✓		Annular Ring	
TKDPZT-BL		✓	✓		Back Light	
TKDPZT-D		✓	✓		Dual Point	
TKDPZT-LV2		✓	✓			✓
TKPZT-A		✓	✓		Annular Ring	
TKPZT-BL		✓	4		Back Light	
TKPZT-D		✓	✓		Dual Point	
TKPZT-LV2		✓	4			4
TKPZTO-A		✓			Annular Ring	
TKPZTO-BL		✓			Back Light	
TKPZTO-D		✓			Dual Point	
TKPZTO-LV2		✓				4

ProZoom® 6.5 Trinocular with Ultra-Cam II™

At the heart of every ProZoom® 6.5 trinocular system is our exclusive 5MP Hybrid HDMI/USB Camera with Onboard Image Controls. This system includes microscope, base assembly, LED ring light, 5MP Hybrid HDMI/USB Camera as well as our FREE HD2 Advanced Imaging & Measurement Software Suite. (a \$595 value)



ProZoom® 6.5 Trinocular with Ultra-Cam II™ and 22" LED Monitor

This system includes all of the features and benefits shown for the TKDPZT-LV2 system, but also includes a 22" HD LED screen. We have matched the specifications of this screen to

5MP Camera. Not all flat screens are created equal

Also Available with 12.1" Integrated Screen! (TKPZT-HU-LV2)



